

# 1/2" Pneumatic Impact Wrench

Best pneumatic tool for heavy duty applications for Car repair and maintenance workshops. Very powerful and adjustable speed controls. High performance twin hammer mechanism which is vibration free even in under load.

TECHNICAL SPECIFICATIONS		
Sq. Dr		1/2"
Free Speed	RPM	8000
Max Torque	ft-LB	»550
	NM	746
Net Weight		2.7 kg
Air Inlet		1/4"
Anvil Length		1"
Air Consumption	CFM	8.83
	M3/min	0.25
Air Pressure		90 Psi, 6.2 Bar
Sound Pressure	dB(A)	99
Mechanism		Twin
Hose Size		3/8"
Exhaust system		Front



# 1/2" Pneumatic Impact Wrench - Short

TECHNICAL SPECIFICATIONS		
Sq. Dr		1/2"
Free Speed	RPM	10000
Max Torque	ft-LB	»550
	NM	746
Net Weight		2 kg
Air Inlet		1/4"
Anvil Length		1" (25.4mm)
Air Consumption	CFM	9.89
	M3/min	0.28
Air Pressure		90 Psi, 6.2 Bar
Sound Pressure	dB(A)	100
Mechanism		Twin
Hose Size		3/8"
Exhaust system		Handle



Sockets



QRC & Couplers



Hoses



1/2 FRL SA