

## Tyre Inflators

Art No : AX 3101099



Art No : AX 3101098

- Robust composite body with backlit LCD digital display & The dial with white numbers against a black background can be read clearly
- Select between bar, psi, kg/cm<sup>2</sup> and kPa.
- Feature built-in LED work light for use in low visibility areas, auto power off to preserve battery life.
- Supplied with 350mm rubber hose and clip on connector
- Air supply Maximum 18bar, 255psi, 18kg/cm<sup>2</sup>, 1800 kpa.
- Air connection with coupling DN 7,2. Inlet : ¼ BSP
- Meets the highest quality and performance demands in professional daily use at tire assemblers, motor vehicle service garages, fleets and in racing environments
- Also suitable for inflating with nitrogen

## Jump Strarter

Art No : AX 3101100

Professional jump starter for mobile slave starting of vehicles with 12V/22Ah electrical system.

Includes a high-quality, powerful starter battery  
Fully insulated, angled solid clamps with long, highly flexible cables.

Display for checking the charge status of the internal battery and vehicle battery.

Protection against power surges

Peak rating : 900amps Cranking rating : 350amps.

Internal charger :Yes AC cord provided :Yes



Flat platform housing provides a lower center of gravity, adding stability, helping to prevent the unit from being accidentally knocked over.

Number 4 Gauge 50" cables maximize the possibility of the unit being positioned on a flat surface while in use.

Easy to read battery indicators provide instant clear feedback as to the status of the battery and uses steel clamps.

Added safety

Easily replaceable short circuit/overload protection, Protection against power surges.

Removal of potential battery gases using and ventilation.